

ESS Mobile ESS with EV Charger

(15kW~60kW/32kWh~60kWh)



GBT or
CCS1/CCS2/CHAdeMO



Solar/Storage/Charger
with DC Coupling



Integrated LiFePO4
Battery/PV/Charger Module



Battery, PV and Charger by
DC Coupling



Technical datasheet

Model	32kWh+15kW	48kWh+25kW	50kWh+40kW	60kWh+60kW
Battery Model	32kWh+15kW-1 Gun	48kWh+25kW-1 Gun	50kWh+40kW-1 Gun	60kWh+60kW-2 Guns
Rated Energy	32kWh	48kWh	50kWh	60kWh
Fast Charger Power	15kW	25kW	40kW	60kW
Max.Recharge DC Power	/	/	20kW	30kW
Max.Recharge AC Power	15kW	20kW	30kW	30kW
Max.Recharge PV Power	15kW	30kW	35kW	35kW
IP Grade	IP54	IP54	IP54	IP54
Communication	R485(WiFi/4G optional)	R485(WiFi/4G optional)	R485(WiFi/4G optional)	R485(WiFi/4G optional)
Size(mm)	680*1000*1200mm	680*1000*1600mm	680*1000*1700mm	680*1000*1950mm
Weight(kg)	500kg(about)	700kg(about)	700kg(about)	850kg(about)



HONGYANG GROUP CO.,LTD.

NO.3,Gaoxiang Road, Gaoxiang industrial area, Ouhai District,Wenzhou Zhejiang,China

0086-13906672098 wells@chinahongyang.com Http://www.chinahongyang.com

